



CHEMICALS

UNIGAWA® Industrial Rubber Hose

GENERAL PURPOSE HOSE



Common Applications

A good quality, general purpose hose for industrial and agricultural service, compressor lines, hot air & water, low pressure spray and many other light chemical application, one copper static wire is available.

Tube

Black EPDM rubber.

Reinforcement

High strength polyester braided incorporating a copper anti-static wire.

Cover

Yellow EPDM rubber, smooth surface, ozone and chemical resistant.

Temperature Range

- 30°C to + 100°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RCD 4006	1/4	6.4	14.0	20 / 60	0.18	0.033	100
RCD 4008	5/16	8.0	16.0	20 / 60	0.22	0.040	100
RCD 4010	3/8	9.5	18.0	20 / 60	0.27	0.052	100
RCD 4013	1/2	12.7	22.0	20 / 60	0.37	0.077	100
RCD 4016	5/8	16.0	26.0	20 / 60	0.48	0.107	100
RCD 4019	3/4	19.0	30.0	20 / 60	0.62	0.130	100
RCD 4025	1	25.4	36.0	20 / 60	0.75	0.127	60

• Other sizes, colours and lengths available on request.