

GENERAL PURPOSE SUCTION & DISCHARGE HOSE (EPDM)



CHEMICALS

Common Applications

Hardwall hose designed to handle a wide range of chemical products, acids and bases. It is specially recommended to convey industrial waters and for usage in water purification systems.

Tube

Black, smooth, EPDM rubber.

Reinforcement

High strength synthetic cord plus steel helix wire and anti-static wire.

Cover

Black, smooth (wrapped finish), EPDM rubber, resistant to chemical products, abrasion, weather and ozone.

Branding

With Green/White **UNIGAWA®** stripe.

Temperature Range

- 40°C to + 100°C.

Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M ³	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(30 Mt)	Mt
RCS 3025	1	25.4	37.0	10 / 30	0.98	0.068	30 / 60
RCS 3032	1 1/4	32.0	44.0	10 / 30	1.18	0.094	30 / 60
RCS 3038	1 1/2	38.0	51.0	10 / 30	1.51	0.133	30 / 60
RCS 3050	2	50.8	65.0	10 / 30	2.19	0.260	30 / 60
RCS 3075	3	76.2	92.0	10 / 30	3.77	0.507	30 / 60
RCS 3100	4	101.6	120.0	10 / 30	5.46	1.080	30 / 60

• Other sizes, colours and lengths available on request.

UNIGAWA® Industrial Rubber Hose