

FOOD DELIVERY HOSE *Non-fatty food liquids*



FOOD

Common Applications

Softwall hose for delivery of water, wine, juice, soft drinks, and other foodstuffs when a food quality hose is required. Not recommended for oily or fatty liquids. (Max 110°C for a few minutes with steam; max 30°C for a few minutes with 1% peracetic acid, 2% phosphoric acid, 5% caustic soda.)

Tube

White, smooth, F.D.A. approved EPDM rubber.

Reinforcement

High strength synthetic cord.

Cover

Oxred, (wrapped finish), EPDM rubber, weather resistance.

Branding

With Purple/Black **UNIGAWA**® stripe.

Temperature Range

- 35°C to + 100°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RFD 1013	1/2	13.0	24.0	10 / 30	0.45	0.035	30 / 60
RFD 1019	3/4	19.0	30.0	10 / 30	0.60	0.037	30 / 60
RFD 1025	1	25.4	37.0	10 / 30	0.83	0.068	30 / 60
RFD 1032	1 1/4	32.0	44.0	10 / 30	1.02	0.104	30 / 60
RFD 1038	1 1/2	38.0	52.0	10 / 30	1.41	0.133	30 / 60
RFD 1050	2	50.8	66.0	10 / 30	1.96	0.268	30 / 60
RFD 1065	2 1/2	63.5	80.0	10 / 30	2.65	0.355	30 / 60
RFD 1075	3	76.2	94.0	10 / 30	3.42	0.529	30 / 60

- Other sizes, colours and lengths available on request.

UNIGAWA® Industrial Rubber Hose