



**HOT**

## PREMIUM RADIATOR HOSE



### Common Applications

Mandrel built straight radiator hose for the transfer of water in motor cooling systems.

#### Tube

Black EPDM rubber, heat resistant.

#### Reinforcement

Piles of high strength polyester cord.

#### Cover

Black EPDM Rubber, wrapped surface, heat and weather resistant.

#### Branding

With Green/Yellow **UNIGAWA**® stripe.

#### Temperature Range

- 30°C to + 120°C.

#### Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M <sup>3</sup>	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(1 Mt)	Mt
RSD 1025	1	25.4	35.0	10 / 30	0.60	0.001	1
RSD 1028	1 1/8	28.0	38.0	10 / 30	0.66	0.001	1
RSD 1032	1 1/4	32.0	42.0	10 / 30	0.74	0.002	1
RSD 1035	1 3/8	35.0	45.0	10 / 30	0.80	0.002	1
RSD 1038	1 1/2	38.0	48.0	10 / 30	0.86	0.002	1
RSD 1041	1 5/8	41.0	51.0	10 / 30	0.92	0.003	1
RSD 1044	1 3/4	44.0	55.0	10 / 30	1.09	0.003	1
RSD 1048	1 7/8	48.0	58.0	10 / 30	1.06	0.003	1
RSD 1050	2	50.8	62.0	10 / 30	1.24	0.004	1
RSD 1054	2 1/8	54.0	65.0	10 / 30	1.31	0.004	1
RSD 1057	2 1/4	58.0	69.0	10 / 30	1.40	0.005	1
RSD 1060	2 3/8	60.0	72.0	10 / 30	1.59	0.005	1
RSD 1065	2 1/2	63.5	76.0	10 / 30	1.68	0.006	1
RSD 1067	2 5/8	67.0	78.0	10 / 30	1.60	0.006	1
RSD 1070	2 3/4	70.0	82.0	10 / 30	1.83	0.007	1
RSD 1073	2 7/8	73.0	85.0	10 / 30	1.90	0.007	1
RSD 1075	3	76.2	88.0	10 / 30	1.97	0.008	1
RSD 1090	3 1/2	89.0	103.0	10 / 30	2.69	0.011	1
RSD 1100	4	101.6	114.0	10 / 30	2.60	0.013	1
RSD 1115	4 1/2	115.0	128.0	10 / 30	2.91	0.016	1
RSD 1125	5	127.0	140.0	10 / 30	3.48	0.020	1

• Other sizes, colours and lengths available on request.