

## VICTORIA LL STEAM HOSE 210°C



**HOT**

### Common Applications

Hardwall hose with steel cord reinforcement for saturated steam at a maximum working pressure 18 bar, used in the chemical industry, petrochemical and industrial applications in general, where a particular bending radius is necessary. Not recommended for steam cleaner. The hose can be used for peaks of superheated steam at 230°C and at 18 bar.

*Attention: the use of superheated steam reduces the hose life span. For longer life drain after used.*

### Tube

Black, smooth, EPDM rubber, resistant to saturated steam.

### Reinforcement

inserts of steel wire and helix wire.

### Cover

Red, pin-pricked, smooth (wrapped finish), EPDM rubber with excellent resistance to high temperatures, weathering, abrasion and ageing.

### Branding

With Black **UNIGAWA®** printing.

### Temperature Range

- 40°C to + 210°C.

### Safety Factor

10 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M <sup>3</sup> (60 Mt)	Coil Length Mt
RSS 1025	1	25.4	39.5	18 / 180	1.24	0.211	60 / 120
RSS 1072	1 1/4	32.0	48.0	18 / 180	1.62	0.298	60 / 120
RSS 1038	1 1/2	38.0	56.0	18 / 180	2.18	0.460	60 / 120
RSS 1050	2	50.8	69.0	18 / 180	3.03	0.502	60 / 120
RSS 1065	2 1/2	63.5	85.5	18 / 180	4.60	0.576	60 / 120
RSS 1075	3	76.2	98.0	18 / 180	5.48	1.200	60 / 120

• Other sizes, colours and lengths available on request.

**UNIGAWA®** Industrial Rubber Hose