

BULK MATERIALS SUCTION HOSE - (FDA)



MATERIAL HANDLING

Common Applications

Hardwall hose with anti-abrasive white FDA approved tube, suitable to convey with pneumatic systems abrasive foodstuff, dust, and PVC grains that must not be stained.

Tube

White, smooth FDA approved NR rubber, resistant to abrasive dust and foodstuff.

Reinforcement

High strength polyester cord plus helix wire and anti-static wire.

Cover

Black NR / SBR rubber, wrapped surface, weather and abrasion resistant.

Branding

With Yellow/White **UNIGAWA**® stripe.

Temperature Range

- 30°C to + 70°C.

Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M ³	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(30 Mt)	Mt
RHS 2050	2	50.8	65.0	10 / 30	1.90	0.260	30 / 60
RHS 2065	2½	63.5	79.0	10 / 30	2.57	0.342	30 / 60
RHS 2075	3	76.2	92.0	10 / 30	3.13	0.950	30 / 60
RHS 2100	4	101.6	120.0	10 / 30	5.25	1.080	30 / 60

• Other sizes, colours and lengths available on request.

UNIGAWA® Industrial Rubber Hose