

CONCRETE PLACEMENT HOSE (4 steel plies, 85 bar W.P.)



Common Applications

Steel cord hose used for concrete placement at casting locations; it is used at the end of the pumps to distribute the concrete. The hose resists suction during the cleaning process. Usually supplied with swaged on "Full flow" hardened couplings.

Tube

Black, smooth, NR/SBR rubber, that withstands the abrasive action of the concrete.

Reinforcement

Plies of steel wire cord.

Cover

Black, smooth, (wrapped finish), NR/SBR rubber, abrasion and weather resistant.

Branding

Continuous red spiral stripe "IVG Abr"

Temperature Range

- 40°C to + 70°C.

Safety Factor

2.5 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RHD 3050	2	50.8	75.0	85 / 200	3.87	0.329	30 / 60
RHD 3075	3	76.2	100.0	85 / 200	5.41	0.992	30 / 60
RHD 3100	4	101.6	128.0	85 / 200	7.66	1.450	30 / 60
RHD 3125	5	127.0	150.0	85 / 200	8.69	2.400	30
RHD 3150	6	152.4	184.0	85 / 175	14.25	2.795	30

• Other sizes, colours and lengths available on request.



MATERIAL HANDLING

UNIGAWA® Industrial Rubber Hose