


BUNKERING HOSE 15 BAR (Complies to EN1765 type S15)



PETROLEUM

Common Applications

Hardwall hose used for the suction and discharge of petroleum products from tankers and barges, bunkering service and industrial applications; suitable for aromatic content up to 50%. Available with swaged-on fittings or built-in fittings.

Tube

Black NBR rubber, oil resistant.

Reinforcement

High strength synthetic cord, steel helix wire and anti-static copper wire.

Cover

Black, smooth (wrapped finish), synthetic rubber resistant to weather, oil and sea water.

Branding

With Brown/White **UNIGAWA**[®] stripe.

Temperature Range

- 20°C to + 82°C.

Electrical characteristics

Electrically continuous.

Safety Factor

4 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M ³ (30 Mt)	Coil Length
	inch	mm	mm				
RPS 4075	3	76.2	96.0	15 / 60	4.04	0.529	30 / 60
RPS 4100	4	101.6	126.0	15 / 60	6.50	1.152	30 / 60
RPS 4150	6	152.4	184.0	15 / 60	12.59	2.795	30 / 60
RPD 4200	8	203.2	238.0	15 / 60	18.55	6.024	30 / 40

• Other sizes, colours and lengths available on request.

UNIGAWA[®] Industrial Rubber Hose