



PETROLEUM

UNIGAWA® Industrial Rubber Hose

FUEL INJECTION HOSE (complies to SAE J30 R9)

UNIGAWA® FUEL INJECTION HOSE W/P 15 BAR



Common Applications

Designed for use in vehicle fuel systems for the transfer of petroleum product.

Tube

Black NBR / SBR rubber, heat & oil resistant.

Reinforcement

High strength synthetic polyester braided.

Cover

Black NBR / EPDM rubber, smooth surface, heat & oil mist resistant.

Branding

With **UNIGAWA®** White printing.

Temperature Range

- 30°C to + 150°C.

Safety Factor

4 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume	Coil Length
	inch	mm	mm	Bar	Kg/Mt	M ³	Mt
RPD 2005/R9	3/16	5.0	10.5	15 / 60	0.10	0.024	100
RPD 2006/R9	1/4	6.5	13.0	15 / 60	0.15	0.028	100
RPD 2008/R9	5/16	7.5	14.6	15 / 60	0.18	0.035	100
RPD 2010/R9	3/8	9.5	16.0	15 / 60	0.19	0.040	100
RPD 2013/R9	1/2	12.7	20.0	15 / 60	0.28	0.061	100
RPD 2016/R9	5/8	16.0	24.0	15 / 60	0.37	0.093	100
RPD 2019/R9	3/4	19.0	28.5	15 / 60	0.53	0.130	100
RPD 2025/R9	1	25.4	35.0	15 / 60	0.68	0.127	60

• Other sizes, colours and lengths available on request.