



PETROLEUM

UNIGAWA® Industrial Rubber Hose

TRANSMISSION OIL HOSE

UNIGAWA® TRANSMISSION OIL HOSE W/P 15 BAR



Common Applications

Suitable for transfer most of the lubrication oils. Under high temperature level. Not recommend for gasoline usage.

Tube

Black NBR / IIR rubber, heat & oil resistant rubber.

Reinforcement

High strength synthetic polyester braided.

Cover

Black NBR / NBR PVC rubber, smooth surface, heat & oil resistant.

Branding

With UNIGAWA® White printing.

Temperature Range

- 20°C to + 135°C.

Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume	Coil Length
	inch	mm	mm	Bar	Kg/Mt	M ³	Mt
RPD 4006	1/4	6.4	14.0	15 / 45	0.18	0.033	100
RPD 4008	5/16	8.0	15.0	15 / 45	0.19	0.035	100
RPD 4010	3/8	9.5	17.0	15 / 45	0.23	0.043	100
RPD 4013	1/2	12.7	21.0	15 / 45	0.32	0.070	100
RPD 4016	5/8	16.0	25.0	15 / 45	0.41	0.093	100
RPD 4019	3/4	19.0	29.0	15 / 45	0.55	0.130	100
RPD 4025	1	25.4	36.0	15 / 45	0.73	0.127	60

• Other sizes, colours and lengths available on request.