

WATER DISCHARGE HOSE (Collapsible)



WATER

Common Applications

Medium duty mandrel built rubber hose is suitable for general purpose industrial water transfer applications.

Tube

Black SBR / NR rubber.

Reinforcement

Multi-ply of high strength polyester cords.

Cover

Black SBR / EPDM rubber, wrapped surface, abrasion and weather resistant.

Branding

With Blue/Black **UNIGAWA**® stripe.

Temperature Range

- 20°C to + 70°C.

Safety Factor

3:1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M ³	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(30 Mt)	Mt
RWD 1025	1	25.4	34.0	10 / 30	0.68	0.056	30 / 60
RWD 1032	1 1/4	32.0	42.0	10 / 30	1.00	0.092	30 / 60
RWD 1038	1 1/2	38.0	48.0	10 / 30	1.03	0.114	30 / 60
RWD 1050	2	50.8	61.0	10 / 30	1.51	0.120	30 / 60
RWD 1065	2 1/2	63.5	74.0	10 / 30	1.83	0.130	30 / 60
RWD 1075	3	76.2	88.0	10 / 30	2.61	0.170	30 / 60
RWD 1100	4	101.6	114.0	10 / 30	3.44	0.210	30 / 60

• Other sizes, colours and lengths available on request.

UNIGAWA® Industrial Rubber Hose