



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 3 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.



**X-P026**

For load pin replacement



**8-P025T**

For trigger replacement

## G-100 Clevis Self Locking Hook

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)					N.W. kg
	mm		A	H	K	P	T	
<b>X-026-06</b>	6	1.4	6	19	93	28	15	0.4
<b>X-026-07</b>	7, 8	2.5	9	24	119	34	20	0.9
<b>X-026-10</b>	10	4.0	11	30	142	44	26	1.4
<b>X-026-13</b>	13	6.7	14	39	178	51	30	3.0
<b>X-026-16</b>	16	10.0	18	49	213	60	36	5.0
<b>X-026-20</b>	20	16.0	21	65	244	70	53	11.0
<b>X-026-22</b>	22	19.0	24	63	273	80	49	13.5

★ Design factor 4:1 proof tested and certified.