



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 2 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.



8-P044
Repair kit available

G-100 Eye Sling Hook with Latch

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)						N.W. kg
	mm		A	D	H	K	P1	T	
X-044/S-06	6	1.4	20	10	19	80	23	17	0.3
X-044/S-07	7, 8	2.5	25	12	23	98	28	20	0.5
X-044/S-10	10	4.0	32	15	31	121	36	23	1.0
X-044/S-13	13	6.7	40	18	38	152	40	27	1.8
X-044/S-16	16	10.0	50	22	45	185	44	32	3.4
X-044/S-20	20	16.0	61	27	64	230	54	48	7.3
X-044/S-22	22	19.0	51	31	63	245	76	52	9.3
X-044/S-26	26	26.5	65	35	80	279	77	60	13.5
X-044/S-32	32	40.0	88	40	86	352	114	65	22.0

★ Design factor 4:1 proof tested and certified.