



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 1 and ASTM A952/ A952M, DIN PAS 1061.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 80 and Grade 100 chain.



Repair kit available for maintenance.

## G-100 Connecting Link

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)				N.W. kg
	mm		A	B	D	K	
<b>X-015-06</b>	6	1.4	15	18	7	45	0.08
<b>X-015-07</b>	7, 8	2.5	18	25	9	59	0.2
<b>X-015-10</b>	10	4.0	25	28	11	69	0.3
<b>X-015-13</b>	13	6.7	30	38	16	92	0.7
<b>X-015-16</b>	16	10.0	36	41	19	101	1.2
<b>X-015-20</b>	20	16.0	42	50	23	122	2.1
<b>X-015-22</b>	22	19.0	49	63	24	152	3.5
<b>X-015-26</b>	26	26.5	55	66	30	162	4.8
<b>X-015-32</b>	32	40.0	69	85	36	203	9.0

★ Design factor 4:1 proof tested and certified.